

ISH PRIME

ISH-TM10R-78H

620-650 WATT

Bifacial Module With Dual Glass


Product of **INDIA**

12 Years
Product Warranty

30 Years
Linear Power Warranty

1%
First-Year Degradation

0.4%
Annual Degradation
(Over 30 years)



CERTIFICATIONS



IS 14286 (Part 1/ Sec 1): 2023
IS/IEC 61730-1:2023
IS/IEC 61730-2:2023

IEC 61215-1-1:2021
IEC 62804 - PID
IEC 61701 - Salt mist corrosion



9001:2015
14001:2015
45001:2018



N-Type Technology

Up to 30% Additional Power Gain when compared with conventional P-type module



Higher Power Generation

Excellent anti-PID performance via optimized process and materials control. Lower susceptibility to LID & LETID



Lower LCOE

Lower balance of systems cost. Improved value proposition of the product with competitive ROI



0% Negative Power Tolerance

Positive power tolerance of upto 0~ 4.99Wp. Module current binning radically reduces string mismatch losses



Rigorous Testing Criteria

Four Stage EL inspection by AI to ensures high quality defect free Solar modules



Optimized Heat Resistance

Optimized temperature co-efficient via advanced graphical patterned busbar and multi cell technology



Electrical Data At 1000W/m², 25° C, Ambient Temperature, 1.5 m/s Wind Velocity

Model Name	ISHTM10R78H620	ISHTM10R78H625	ISHTM10R78H630	ISHTM10R78H635	ISHTM10R78H640	ISHTM10R78H645	ISHTM10R78H650
Peak Power Pmax (Wp)	620	625	630	635	640	645	650
Max Voltage Vmpp (V)	47.54	47.71	47.88	48.05	48.22	48.39	48.54
Max Current Imp (A)	13.05	13.10	13.16	13.22	13.28	13.34	13.40
Open Circuit Voltage Voc (V)	56.60	56.80	57.00	57.20	57.40	57.60	57.80
Short Circuit Current Isc (A)	13.70	13.74	13.78	13.82	13.86	13.90	13.94
Module Efficiency (%)	22.18	22.36	22.53	22.71	22.90	23.08	23.26

Electrical Data At NOCT At 800W/m², 20° C, Ambient Temperature, 1 m/s Wind Velocity

Peak Power Pmax (Wp)	466.28	470.07	473.86	477.59	481.33	485.08	488.85
Max Voltage Vmpp (V)	44.24	44.43	44.62	44.76	44.9	45.04	45.18
Max Current Imp (A)	10.54	10.58	10.62	10.67	10.72	10.77	10.82
Open Circuit Voltage Voc (V)	53.77	53.96	54.15	54.34	54.53	54.72	54.94
Short Circuit Current Isc (A)	11.06	11.09	11.13	11.16	11.19	11.21	11.24

Electrical Characteristics With Different Rear Side Power Gain

Pmax (Wp)	651	656	661	666	672	677	682
Efficiency (5%)	23.28	23.47	23.65	23.84	24.04	24.23	24.42
Pmax (Wp)	713	718	724	730	736	741	747
Efficiency (15%)	25.5	25.71	25.9	26.11	26.33	26.54	26.74
Pmax (Wp)	775	781	787	793	800	806	812
Efficiency (25%)	27.72	27.95	28.16	28.38	28.62	28.85	29.07

The additional gain from the rear side compared to the power of the front side at the standard test condition. It depends on mounting (structure, height, tilt angle etc.) and albedo of the ground.

Operating Condition

Power Tolerance	0~+5W
Maximum System Voltage	1500
Maximum Series Fuse Rating	30A
Nominal Operating Cell Temperature (NOCT)	42±2 °C
Max. Surface Load Capacity, Pa	5400
Max. Wind Speed Capacity, Pa	2400
Safety Class	Class II
Hail Impact Velocity, m/sec	23

Mechanical Characteristics

Cell Type	N-Type TOPCon
No. Of Cells	156 (78 x 2) Pcs
Dimensions	2465 x 1134 x 35mm
Weight	33.8 kg
Front Glass	2.0 mm, Low Iron, Heat Strengthened AR Coated
Back Glass	2.0 mm, Low Iron, Heat Strengthened Glass
Frame	T6 Anodized Aluminum Alloy
Junction Box	IP 68, Split Junction Box With Individual Bypass Diodes
Output Cables	4.0 mm ² (+): 400mm, (-): 400mm Or Customized Length


Packaging Configuration

Container	40'HC	
Height Of Modules (mm)	35	30
Number Of Modules Per Pallet	31	36
Number Of Pallets Per Container	16	16
Number Of Modules Per Container	496	576



TEMPERATURE COEFFICIENTS

Tc Of Open Circuit Voltage (B)	-0.27% /°C
Tc Of Short Circuit Current (A)	0.045% /°C
Tc Of Power (r)	-0.3% /°C
Temperature Range	-40°C To+85°C

Power-Voltage Curves (ISHTM10R78H650)



Current-Voltage Curves (ISHTM10R78H650)



Linear Performance Warranty

